Carpasol

Carpet cleaner for spray extraction machines

- Cleans carpets deep into the fibres
- Quickly dissolves the dirt
- Forms vacuumable agglomerates composed of polymers and dirt particles
- Agglomerates do not stick to the carpet fibres (anti-soil effect)
- Can also be used with the textile pad method

Area of application

Can be used on colourfast and moisture-resistant textile floor coverings and covers.

Application

Please test on a small inconspicuous spot before first application. Vacuum the carpet thoroughly first.

Spray extraction:
Depending on the degree of soiling, 0.5–1 L to 8 L of cold water.
Pour cleaning solution into the freshwater tank. Pre-spray stains with the floor nozzle. Move the floor nozzle over the carpet in parallel, overlapping paths. Fluff up carpet pile and do not walk on until fully dry. Consumption: 100.0 ml/m^2.

Textile pad method:
Depending on the degree of soiling, 100–150 ml to 1 L of cold water.
Pour cleaning solution into the spray can. Spray textile pad with cleaning solution and place under rotary floor machine. Spray sparingly onto approx. 1m^2 of carpet and work in circular motions. Turn over or replace soiled textile pad.
Consumption: 5.0 ml/m^2.

Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, anionic surfactants < 5%, phosphates 5–15%, maintenance substances, water-soluble solvents, fragrances.
pH value (concentrate): approx. 9.5 pH value (ready-to-use solution): approx. 8.5

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j600510	10 L canister	60
j600572	200 L drum	2

www.kiehl-group.com